

LYON®

ALL-WELDED EXTREME LOCKERS



CONFIGURATIONS

Single Tier Quiet Lockers

W: 9, 12, 15, 18
D: 12, 15, 18, 21, 24
H: 60*, 72*

W: 12, 15
D: 12, 15, 18
H: 37*

(actual 37-1/32)

W: 12, 15
D: 15, 18
H: 48*

(actual 48-5/8)



Double Tier Quiet Lockers

W: 9, 12, 15, 18
D: 12, 15, 18, 21, 24
H: 30*, 36*



Triple Tier Quiet Lockers

W: 9, 12, 15
D: 12, 15, 18, 21
H: 20*, 24*



Multiple Tier Lockers

Four Tier Lockers

W: 12, 15
D: 12, 15, 18, 21
H: 15*, 18*

Five and Six Tier Lockers

W: 12, 15
D: 12, 15, 18, 21
H: 12*



FEATURES

- Lockbars feature nano roller latching fingers that engage 12-gauge door jambs for maximum security
- High security single point latches are designed for built-in locks with wrap around technology. Includes padlock hasp
- The door frames are formed by overlapping and welding the junction between the horizontal and vertical members to form a rigid unitized structure that fully frames the door
- Full height continuous hinges
- Door frames include integral full height 16-gauge door strikes to reinforce door edges
- One piece doors formed from 14-gauge prime, high grade class 1 steel
- Three latch points on single tier doors and two on double and triple tier doors
- One piece recessed handle pockets add strength to the handle area and eliminate the vulnerable seams of formed handles. Stainless steel or die cast recessed or cremone turn handle
- Soft rubber bumpers, at door jamb locations, cushion door slams
- 16-gauge bottom channel reinforcement
- 18-gauge pan reinforcement on door

HANDLE OPTIONS



Stainless Steel Recessed Handles*

with finger lift offers added safety and security with a clean flush mount appearance. Standard on single, double and triple-tier lockers. Option available for zinc alloy.



Single Point Recessed Handle Latching System

operates with no additional moving parts. Available on single, double and triple-tier lockers. Not available on 9" wide lockers. Option available for zinc alloy. Additional cost option.



Pull Handles

with built-in padlock loop are standard on multiple tier lockers. Optional roll point catch available.



AVAILABLE
OPTION

Cremone Turn Handles

with built-in padlock loop, are not available on doors larger than 20" high



Tamper Guard Handles*

have built-in padlock loop and slim profile. Available on single, double and triple-tier lockers.

*Add 6" to overall height for legs when included.

*Lyon lockbar is standard.

Body - 16-gauge steel, flanged to give double thickness of metal at back vertical corners. 18-gauge backs. Bottoms shall have a 16-gauge channel reinforcement from front to back.

Door Frame - 16-gauge formed steel channels. Vertical members shall have an additional flange to form continuous door strike. Corners shall be lapped and welded into a rigid assembly. In addition, bottom cross members shall have tang at each end that fits through slot in rear flange of upright frame member to prevent twisting out of alignment. Top and bottom cross members shall provide support for front edge of locker top and locker bottom.

Door - One-piece, 14-gauge steel on single, double and triple tier with both vertical edges formed into channel-shaped formation; top and bottom shall be flanged at 90 degree angle. On multiple tier lockers, hinge side shall be formed into channel shaped formation with other three sides flanged at 90 degree angle. An 18-gauge pan stiffener will be welded inside the channel - shaped formation of the hinge side of the door. Stiffeners shall be 1" wide on 12" wide doors, 3-1/2" wide on 15" and 18" wide doors, and 7-1/2" wide on 24" wide doors.

Ventilation - Louvers shall be provided as follows:

Locker Styles

Single/Double tier lockers - 9"w
Single tier lockers - Over 9"w
Double tier lockers - Over 9"w
Triple tier lockers - 9"w
Triple tier lockers - Over 9"w
Multiple tier lockers

Louvers

Six 3-1/2" louvers top and bottom
Six 6" louvers top and bottom
Six 6" louvers top and bottom
Two 3-1/2" louvers top and bottom
Two 6" louvers top and bottom
Three 3-1/2" louvers per door for 12" and 15" wide lockers
Four 6" louvers per door for lockers 18" wide and over

Door Jambs - 48" and higher single tier lockers shall have three door jambs; double tier and triple tier lockers shall have two jambs welded to side of door frames to engage locking device. Design and gauge of jamb shall prevent freeing of locking device by prying. Each jamb shall have easily replaceable soft rubber bumper.

Hinges - Shall be full height continuous.

Quiet Locking Device - Single tier locking device shall engage frame at three points; double tier and triple tier at two points. Channel shaped locking device with full length reinforcing ribs shall be a quiet design utilizing nylon guide inserts to reduce metal to metal contact. The locking device shall include a latch finger that engages the 12-gauge door jamb. Lock bar shall be enclosed on three sides and operate within the channel formation of the door. Locking device shall be prelocking so mechanism can be locked in open position - door locking automatically when closed. An optional single point latch shall be available except on 9" wide lockers. Box locker shall have one-point locking device with a 14-gauge lock clip for attaching padlock. Doors also to be provided with lock hole filler to permit use of built in lock.

Handles - On single, double and triple tier lockers, handles shall be stainless steel recessed. No moving parts are to operate against outside surface of locker. Padlock attachment to be integral part of lift which shall be attached directly to locking bar and protected by fixed handle housing. Handle to provide built in padlock strike. The recessed handle shall be 4-1/8"w x 6-1/16"h x 1-1/4"d. Multiple tier lockers shall be equipped with a 16-gauge door pull with padlock attachment when not used with built in locks. Die Cast Recessed and cremone turn handle options available.

Shelves - Single tier lockers shall have one 16-gauge shelf approximately 9" below top. Flanged on all four sides for strength with the front flange turned 45 degrees for safety and attached at no less than two points through each side flange. Only single tier lockers 48" and taller have shelves.

Coat Hooks - Single tier, double tier and triple tier lockers shall have one double prong hook and three single prong wall hooks. All hooks to be zinc-plated or subjected to a comparable rust retardant treatment and attached with two nuts and bolts.

Number Plates - Optional aluminum number plates with etched figures at least 3/8" high. All lockers shall have number plates attached near top of door.

Standard Finish - Exposed steel parts shall be thoroughly cleaned, given a bonding and rust inhibitive phosphate treatment and then electrostatically sprayed with powder coat.

NOTE: Contact Lyon for finish compatibility with any chemicals.

Anchoring - To prevent tipping or injury, Lyon strongly recommends that lockers be floor and/or wall anchored. "Z" Type Bases are available for lockers without legs.

Recess Trim - End and top recess trim for lockers to be placed in wall recesses shall be 18-gauge formed steel with a 2-3/4" wide face and shall be bolted to locker frames.

Top recess trim to be in approximately 5'0" lengths with a formed splice cap to cover joints and to hold top recess trim in alignment. End recess trim to be 2-3/4" higher than lockers and will lap over ends of top recess trim for a hairline joint at top of corners.

LYON®

ALL-WELDED EXTREME LOCKERS

SPECIFICATION SUMMARY

- 14-gauge door with 16-gauge frame
- 16-gauge body parts with 18-gauge backs
- All seams and joints welded
- Continuous type hinges
- One piece 14-gauge door
- Secure multi-point locking system
- Stainless steel recessed handles (see page 25)
- 16-gauge reinforced bottom channels
- 18-gauge pan reinforcement on door

MATERIAL

Prime, high grade Class 1 mild annealed, cold-rolled steel free from surface imperfections. A.S.T.M.-A1008. Galvannealed steel available for high humidity atmospheres. A.S.T.M.-A653. Bolts to be zinc plated or subjected to other rust-retardant treatment.

General Construction - All lockers shall be pre-assembled, with all seams and joints welded for rigidity and durability.

Quiet-Plus Eliminating metal to metal contact, all Lyon locker doors are fitted with nylon lockbar guides to reduce clanging and provide smoother, quieter operation.

In addition to quieter lock bars, Lyon Quiet-Plus locker doors include a sound deadening door panel. The resulting combination minimizes noise levels caused by opening and closing locker doors.

CSI Formatted Specifications are available at
www.lyonworkspace.com/architects

Note: There are certain sizes and/or types of lockers that are available in minimum quantity production runs only. Contact your Lyon factory representative for complete details.